


DESCRIPTION

• 24 AWG/25 Pair unshielded twisted pair 1000' feet solid copper on wood reels. Cable comes with standard ripcord for stripping jacket and it is marked every two feet so one can see how much cable is left in the box.

FEATURES AND BENEFITS

- Used for Voice communications
- Jacket: Flame - retardant PVC / Sequential footage markings
- Rip Cord is applied longitudinally under jacket
- Verified by third-party for guaranteed performance

APPLICATIONS

- Voice/Telephone/Fast Ethernet
- 10 Base - T
- 100 Base - T4
- 100 Base - X 100 Base - VG
- 4/16 Mbps Token Ring ANSI X3T9.5 TP - PMD (FDDI)
- ATM PMD 155 Mbps

STANDARD COMPLIANCES

- ANSI/TIA 568-C.2
- ANSI/TIA 862 (Building Automation)
- ISO/IEC 11801 Ed. 2.0 (Class EI)
- ICEA 8-102-700 (Category 6 or 5E)
- REACH Compliant
- CPR Compliant (Fully Comply to 305/2011 & EN 50575:2014-09)
- RoHS Compliant Directive 2002/95/EG

Distributed By:
Cables Plus, USA
5608 W Marshall Street
Richmond, VA 23230
www.CablesPlusUSA.com
804-716-9007

Toll Free: (866) 945-5051
Local: (770) 945-5051
Fax: (770) 945-9582
www.commoditycables.com


PHYSICAL PROPERTIES

	CMR (Non-Plenum)
Conductor	Solid Bare Copper
Conductor Diameter (mm)	0.500
Average Thickness (±0.03mm)	0.16
Minimum Point Thickness (mm)	0.15
Unit Lay Length (mm)	500 underneath
Color Tape Lay Length (mm)	<150
Maximum Pulling Force (lbs)	25
Twisting Lay Length	80 underneath
100P Cabling Lay Length (mm)	800 underneath
Installation Dia (±0.05mm)	800 underneath

JACKET		CMR (Non-Plenum)
Filler		Without
Average Thickness (±0.1mm)		0.80
Minimum Point Thickness (mm)		0.65
Before Aging	Tensile Strength (Mpa)	≥13.8
	Elongation (%)	≥100
After Aging	Tensile Strength (Mpa)	≥85% of unaged
	Elongation (%)	≥50% of unaged
Cold Bend (No Crack)		-20±2°Cx4hrs
Temperature Rating		-20°C to +75°C
Max Pull Strength		200N
Aging Condition (°Cxhrs)		100x240
Standard Color		Gray

ELECTRICAL CHARACTERISTICS

Elongation of Conductor	Min 15%
Elongation of Insulation	Min 300%
Tensile Strength of Insulation	Min 6Mpa
Shrinkage of Insulation	Max 5%
Elongation of Jacket (unaged)	Min 200%
Tensile strength of Jacket (unaged)	Min 12Mpa
Capacitance	56pF/km
Capacitance unbalance	500pF/100km
Max. Conductor DC Resistance 20°C	≤93.8
Resistance Unbalance (%)	≤5
Insulation Resistance	5000MΩ-km
Dielectric Strength	DC.1.5kv, 7min

JACKETS ABBREVIATION

Black	B	Last alphabetical character of each part number indicates the color code that the Jacket is available in. For example Part # 6CMR-244Bx ("x" indicates all the colors to the left are available for this product.
White	W	
Gray	G	
Blue	O	
Yellow	Y	
Green	V	
Orange	OR	
Purple	P	
Red	R	
Pink	PI	

1000' Wood Reel
Weight: 100 lbs.

CAT 3 U/UTP CMR 25PAIR/24AWG ELECTRICAL SPECIFICATION

FREQUENCY (MHz)	ATTENUATION (DB/100m)	NEXT (DB)	SRL (DB)	IMPEDANCE (DB/100m)
0.772	2.2	43	12	100 ± 15
1	2.6	41	12	100 ± 15
4	5.6	32	12	100 ± 15
8	8.5	28	12	100 ± 15
10	9.7	26	12	100 ± 15
16	13.1	23	10	100 ± 15

All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice