

EDGE™ Housing 4 rack units, Gray, holds up to 48 EDGE modules or panels

CORNING

**Part Number:
EDGE-04U**

EDGE™ housings are high-density, preterminated fiber optic hardware solutions. They offer industry-leading connector density and easy finger/toolless access to enable faster moves, adds, and changes (MACs). The units can be configured to accommodate 96, 144, 288, or 576 fibers.

EDGE housings can be rack- or cabinet-mounted and are ideal for data centers, local area network (LAN) and storage area network (SAN) applications, as well as enterprise networks.



EDGE™ Housing 4 rack units, Gray, holds up to 48 EDGE modules or panels



EDGE™ Housing, 4 rack units, holds up to 48 EDGE modules or panels

Specifications

General Specifications	
Product Type	Fiber Optic Hardware
Access Type	Front and rear access slidable
Lockable	Yes, rear side
Mounting Type	Rack Mount, Cabinet-mount
Application	Data Center, Data Center LAN/SAN, Enterprise Networks
Brand	EDGE™

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Number of Modules	48
Cable entry type	Side brush entry

EDGE™ Housing 4 rack units, Gray, holds up to 48 EDGE modules or panels

CORNING

Design

Number of Panels/Cassettes per Housing	48
Cable Entry Direction	Rear
Housing Type	EDGE™
Color	Silver
Panel or Cassette Type	EDGE™
Panel or Module Type	EDGE™
Fiber Capacity	576

Design - Adapter

Housing Color	Silver
---------------	--------

Dimensions

Height	177 mm (6.97 in)
Width	432 mm (17.01 in)
Depth	561 mm (22.09 in)

Shipping Dimensions

Height	305 mm (12.01 in)
Width	565 mm (22.24 in)
Depth	660 mm (25.98 in)

Ordering Information

Product Number	EDGE-04U
EAN Code	4056418011516
Weight	14.5 kg

EDGE™ Housing 4 rack units, Gray, holds up to 48 EDGE modules or panels

CORNING

Ordering Information

Package Contents	"EDGE™ Housing 4U; Quick Start Guide, #12-24 and #10-32 mounting screws, Cage Nut Mounting Kit, Velcro Strap, Fiber Optic Warning Label"
Shipping Weight	16.8 kg
Module Capacity	48
Width	432 mm (17.01 in)
Height Unit	4 U
Units per Delivery	1/1
Trunk Capacity	48 (size 1 or 2, double stack cradle)



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2023 Corning Optical Communications. All rights reserved.