


FuseConnect Connectors (SC, FC, LC, ST)



FuseConnect in Fusion Splicer



FuseConnect Kits—ST (blue), SC (green), LC (blue)

## FUSEConnect® Fusion-Spliced, Field-Installable Connectors

AFL's FUSEConnect fusion-spliced, field installable connectors are uniquely designed and feature only four to five components. The factory pre-polished ferrule eliminates the need for polishing, adhesives, and crimping in the field, which minimizes the potential for operator error and expensive connector scrap.

FUSEConnect utilizes a fusion splicer to terminate the connector in the field, addressing return loss concerns present in analog optical networks. This advanced process yields true APC performance for SC/APC and LC/APC configurations, and is compliant to GR-326-CORE. FUSEConnect is compatible with Fujikura fusion splicers and most other fiber holder-based fusion splicing platforms.

### Features

- Field installable
- No adhesives, crimping or polishing
- True APC performance
- MM compliant to TIA/EIA568C.3
- Compatible with most fusion splicers

### Applications

- Connectorization in:
  - RF-overlay FTTP networks
  - Cable TV backbone networks
  - Outside plant
  - FTDD
  - MDU FTTP Cabling
- Central office connector replacement
- Data center installation

### Specifications

PARAMETER	VALUE
Connector Type	SC, LC, FC, ST
Cable Type	900 $\mu$ m, 2 mm, 3 mm
Polish	APC, UPC, PC
Insertion Loss	SM: 0.15 dB (average), 0.3 dB (maximum) / MM: 0.10 dB (average), 0.3 dB (maximum)
Return loss	SM: $\leq$ -65 dB (APC), $\leq$ -55 dB (UPC) / MM: $\leq$ -35 dB (PC)
Operating Temperature	-40°C to +75°C

### Ordering Information

CONN. TYPE	BOOT TYPE	AFL NO.*				
		UPC SM (Blue)	APC SM (Green)	PC 62.5 $\mu$ m MM (Beige)	PC 50 $\mu$ m MM (Black)	PC 50 $\mu$ m LOMMF (AQUA)**
SC	900 $\mu$ m	FUSE-SC9SMU-6	FUSE-SC9SMA-6	FUSE-SC9M62-6	FUSE-SC9M50-6	FUSE-SC9M50L-6
	3 mm	FUSE-SC3SMU-6	FUSE-SC3SMA-6	FUSE-SC3M62-6	FUSE-SC3M50-6	FUSE-SC3M50L-6
LC	900 $\mu$ m	FUSE-LC9SMU-6	FUSE-LC9SMA-6	FUSE-LC9M62-6	FUSE-LC9M50-6	FUSE-LC9M50L-6
	2 mm	FUSE-LC2SMU-6	FUSE-LC2SMA-6	FUSE-LC2M62-6	FUSE-LC2M50-6	FUSE-LC2M50L-6
FC	900 $\mu$ m	FUSE-FC9SMU-6	—	FUSE-FC9M62-6	FUSE-FC9M50-6	FUSE-FC9M50L-6
	2 mm	FUSE-FC2SMU-6	—	FUSE-FC2M62-6	FUSE-FC2M50-6	FUSE-FC2M50L-6
	3 mm	FUSE-FC3SMU-6	—	FUSE-FC3M62-6	FUSE-FC3M50-6	FUSE-FC3M50L-6
ST	900 $\mu$ m	FUSE-ST9SMU-6	—	FUSE-ST9M62-6	FUSE-ST9M50-6	FUSE-ST9M50L-6
	2 mm	FUSE-ST2SMU-6	—	FUSE-ST2M62-6	FUSE-ST2M50-6	FUSE-ST2M50L-6
	3 mm	FUSE-ST3SMU-6	—	FUSE-ST3M62-6	FUSE-ST3M50-6	FUSE-ST3M50L-6

\* AFL NO. is for one pack of 6 pieces

\*\* Laser Optimized MM Fiber (LOMMF) compatible with OM3 and OM4 fibers