



REV	MODIFICATION	UPDATE DATE	SIGNATURE

CONFIDENTIAL

NOTES:
 Insertion loss MTP≤0.35dB LC≤0.2dB
 Return loss MTP≥30dB LC≥35dB



Cable Length	Tolerance
Cable Length<1M	5cm
1M≤Cable Length<15M	10cm
15M≤Cable Length<30M	15cm
Cable Length≥30M	Cable Length*1%

7	1	MTP(Female)/PC MM Elite 12 Fibers 3.0mm Connector (Erika violet Housing Black Boot)
6	4	Channel Marker
5	1	Serial Number Label
4	1	Fanout Kit
3	A/R	OD:2.0mm, Simplex,Erika violet,OFNP
2	4	LC/UPC MM Uniboot Ezconn Connector(Polarity Reversal) (Erika violet Housing White Boot)
1	A/R	Ø3.0mm,Multimode 50/125 OM4,Corning Fiber, 8 Fibers Micro Cable,OFNP, Color:Erika violet

Requirements Of Cable					
Cable Type	3.0mm		Fiber Type	OM4 Corning	
Cable Diameter	3.0mm		Attenuation	@850nm ≤2.3dB/km	
Cable Material	OFNP			@1300nm ≤0.6dB/km	
Tensile Strength	Long Term	80 N	Crush Resistance	Long Term	100 N/100mm
	Short Term	160 N		Short Term	500 N/100mm
Bending Radius	Static	10D	Temperature Range	Storage Temperature	-5 ~ +50
	Dynamic	20D		Operating Temperature	-0 ~ +50

ITEM	QTY	P/N	SPECIFICATIONS		
------	-----	-----	----------------	--	--

	DRAW	DATE	07-04-2023	TITLE: Fiber Optic patch Cord MTP/PC-LC/UPC 8 Fibers Multimode		
	CHECK	APPROVED	CUSTOMER NO	MTF-LCU-08-OM4-xxxM-B	DISTRIBUTED BY	Cables Plus, LLC 5608 W Marshall St, Richmond, VA 23230 - (804) 716-9007 www.CablesPlusUSA.com
1	2	3	4	5	6	REV A