


版次 REV	变更内容 MODIFICATION	变更日期 UPDATE DATE	签名 SIGNATURE



NOTES:
 Insertion loss MTP≤0.35dB LC≤0.2dB
 Return loss MTP≥30dB LC≥35dB

Blue1	Orange2	Green3	Brown4	Grey5	White6	Red7	Black8	Yellow9	Violet10	Pink11	Aqua12	Blue13	Orange14	Green15	Brown16
-------	---------	--------	--------	-------	--------	------	--------	---------	----------	--------	--------	--------	----------	---------	---------

Cable Length	Tolerance
Cable Length<1M	5cm
1M≤Cable Length<15M	10cm
15M≤Cable Length<30M	15cm
Cable Length≥30M	Cable Length*1%

7	1	MTP/APC Female MM Elite 3.0mm 16 Fibers Usconec Connector(Aqua Housing Black Boot)
6	8	Channel Marker
5	1	Serial Number Label
4	1	Fanout Kit
3	A/R	OD:2.0mm, Simplex,Aqua,OFNP
2	8	LC/UPC MM Uniboot Ezconn Connector(Polarity Reversal) (Aqua Housing White Boot)
1	A/R	Ø3.0mm,Multimode 50/125 OM3-300,Corning Fiber. 16 Fibers Micro Cable,OFNP, Color:Aqua

Requirements Of Cable					
Cable Type				Fiber Type	OM3-300 Corning
Cable Diameter	3.0mm		Attenuation	@850nm ≤2.3dB/km	
Cable Material	OFNP			@1300nm ≤0.6dB/km	
Tensile Strength	Long Term	80 N	Crush Resistance	Long Term	100 N/100mm
	Short Term	160 N		Short Term	500 N/100mm
Bending Radius	Static	10D	Temperature Range	Storage Temperature	-5°C ~ +50°C
	Dynamic	20D		Operating Temperature	-0°C ~ +50°C

ITEM	QTY	P/N	SPECIFICATIONS											
Cables Plus USA			DRAW	FJZ	DATE	30-10-2024	TITLE: Fiber Optic patch Cord MTP/APC-LC/UPC 16 Fibers Multimode							
			CHECK	<i>Wuankuan</i>	APPROVED	<i>Kaka Tao</i>	CUSTOMER NO	MTF-LCU-16-OM3-xxxMA		DWG NO	ADT-01-0829-0814-0185		REV	A