



版次 REV	变更内容 MODIFICATION	变更日期 UPDATE DATE	签名 SIGNATURE



Blue1	Orange2	Green3	Brown4	Yellow9	Violet10	Pink11	Aqua12
-------	---------	--------	--------	---------	----------	--------	--------



Cable Length	Tolerance
Cable Length<1M	5cm
1M≤Cable Length<15M	10cm
15M≤Cable Length<30M	15cm
Cable Length≥30M	Cable Length*1%

7	1	MTP(Female)/PC MM Elite 12 Fibers 3.0mm Connector (Aqua Housing Black Boot)
6	4	Channel Marker
5	1	Serial Number Label
4	1	Fanout Kit
3	A/R	OD:2.0mm, Simplex,Aqua,OFNP
2	4	MDC/UPC MM 2.0mm Connector (Aqua Housing Black Boot)
1	A/R	∅3.0mm,Multimode 50/125 OM3-300,Corning Fiber, 8 Fibers Micro Cable,OFNP, Color:Aqua

Requirements Of Cable					
Cable Type				Fiber Type	OM3-300 Corning
Cable Diameter	3.0mm			@850nm ≤2.3dB/km	
Cable Material	OFNP			@1300nm ≤0.6dB/km	
Tensile Strength	Long Term	80 N	Crush Resistance	Long Term	100 N/100mm
	Short Term	160 N		Short Term	500 N/100mm
Bending Radius	Static	10D	Temperature Range	Storage Temperature	-5°C ~ +50°C
	Dynamic	20D		Operating Temperature	-0°C ~ +50°C

ITEM	QTY	P/N	SPECIFICATIONS									
Cables Plus USA			DRAW	YUFENG XIE	DATE	07-04-2023	TITLE: Fiber Optic patch Cord MTP/PC-MDC/UPC 8 Fibers Multimode					
			CHECK	WEN ZHU LUO	APPROVED	Zhenlong Yu	CUSTOMER NO	MTF-MDC-08-OM3-XXXM-B	DWG NO	ADT-01-0829-0813-0075	REV	A