




REV	MODIFICATION	UPDATE DATE	SIGNATURE

Type A




- NOTES:
1. Insertion loss  $\leq 0.35\text{dB}$
  2. Return loss  $\geq 30\text{ dB}$
  3. If the length of optical cable is less than 0.5m, only stick a line label in the middle.



Blue1	Orange2	Green3	Brown4	Grey5	White6	Red7	Black8	Yellow9	Violet10	Pink11	Aqua12	Blue13	Orange14	Green15	Brown16
-------	---------	--------	--------	-------	--------	------	--------	---------	----------	--------	--------	--------	----------	---------	---------

Blue1	Orange2	Green3	Brown4	Grey5	White6	Red7	Black8	Yellow9	Violet10	Pink11	Aqua12	Blue13	Orange14	Green15	Brown16
-------	---------	--------	--------	-------	--------	------	--------	---------	----------	--------	--------	--------	----------	---------	---------



Cable Structure

Cable Length	Tolerance
Cable Length < 1M	5cm
1M ≤ Cable Length < 15M	10cm
15M ≤ Cable Length < 30M	15cm
Cable Length ≥ 30M	Cable Length * 1%

ITEM	QTY	P/N	SPECIFICATIONS
4	2		Cable Lable
3	1		MTP/APC Male MM Elite 16 Fibers 3.0mm Usconec Connector (Lime Green Housing Black Boot)
2	1		MTP/APC Female MM Elite 16 Fibers 3.0mm Usconec Connector (Lime Green Housing Black Boot)
1	A/R		OD:3.0mm,Multimode 50/125 OM5,Corning Fiber, 16Fibers Micro Cable,OFNP, Color:Lime Green

Requirements Of Cable					
Cable Type				Fiber Type	OM5 Corning
Cable Diameter		3.0mm	Attenuation	@850nm ≤2.3dB/km	
Cable Material		OFNP		@1300nm ≤0.6dB/km	
Tensile Strength	Long Term	80 N	Crush Resistance	Long Term	100 N/100mm
	Short Term	160 N		Short Term	500 N/100mm
Bending Radius	Static	10D	Temperature Range	Storage Temperature	-5°C ~ +50°C
	Dynamic	20D		Operating Temperature	-0°C ~ +50°C

Cables Plus USA	DRAW	FJZ	DATE	30-10-2023	TITLE: Fiber Optic Patch Cord MTP/APC-MTP/APC 16Fibers Multimode					
	CHECK	<i>Lihuanhuan</i>	APPROVED	<i>Kaka Tao</i>	CUSTOMER NO	MTF-MTM-16-OM5-xxxMA	DWG NO	ADT-01-0829-0808-0179	REV	A