


版次 REV	变更内容 MODIFICATION	变更日期 UPDATE DATE	签名 SIGNATURE



Blue1	Orange2	Green3	Brown4	Grey5	White6	Red7	Black8	Yellow9	Violet10	Pink11	Aqua12	Blue13	Orange14	Green15	Brown16
-------	---------	--------	--------	-------	--------	------	--------	---------	----------	--------	--------	--------	----------	---------	---------

ITEM	QTY	P/N	SPECIFICATIONS
7	1		MTP/APC Male MM Elite 3.0mm 16 Fibers Usconec Connector(Aqua Housing Black Boot)
6	8		Channel Marker
5	1		Serial Number Label
4	1		Fanout Kit
3	A/R		OD:2.0mm, Simplex,Aqua,OFNP
2	8		LC/UPC MM Uniboot Ezconn Connector(Polarity Reversal) (Aqua Housing White Boot)
1	A/R		Ø3.0mm,Multimode 50/125 OM3-300,Corning Fiber. 16 Fibers Micro Cable,OFNP, Color:Aqua

Requirements Of Cable					
Cable Type				Fiber Type OM3-300 Corning	
Cable Diameter		3.0mm	Attenuation		@850nm ≤2.3dB/km
Cable Material		OFNP	Attenuation		@1300nm ≤0.6dB/km
Tensile Strength	Long Term	80 N	Crush Resistance	Long Term	100 N/100mm
	Short Term	160 N		Short Term	500 N/100mm
Bending Radius	Static	10D	Temperature Range	Storage Temperature	-5°C ~ +50°C
	Dynamic	20D		Operating Temperature	-0°C ~ +50°C

Cables Plus USA		DRAW	FJZ	DATE	30-10-2023	TITLE: Fiber Optic patch Cord MTP/APC-LC/UPC 16 Fibers Multimode				
CHECK		<i>Wuankuan</i>	APPROVED	<i>Kaka Tao</i>	CUSTOMER NO	MTM-LCU-16-OM3-xxxMA	DWG NO	ADT-01-0829-0814-0186	REV	A