

ACCESS RAMPS AND RAILS



ADA COMPLIANT

Cross-Guard™ ADA Compliant Ramps and Rails feature a gentle slope and slip resistant ramps to provide a safe crossing point for wheelchairs, carts and vehicles with small wheels. These ramps and rails can also be used in conjunction with Cross-Link Protector Bridges.

- Compatible with select Linebacker® & Guard Dog® Protectors
- Lightweight, 36" wide, modular ADA compliant ramps
- Quick attachment to one or multiple cable protectors
- Side rails provide ADA compliant edge protection
- Add ramps and rails whenever requirements specify
- Does not prevent accessibility to cables and cords
- One person installation - no tools required

FOR SPECIFIC STYLES OF LINEBACKER® AND GUARD DOG® CABLE PROTECTORS



◀ **Carnival Midway Safety...**
LINEBACKER®
 Cable Protectors and ADA compliant ramps have "Greatly improved the safety and accessibility of our carnival midway" and "are one of the greatest improvements to hit our midway in years."
 - Gehrie Aten, President
 Bill Hames Shows, Inc.

MODEL	DESCRIPTION	COLOR	A-WIDTH	B-LENGTH	C-HEIGHT	WEIGHT
CPADARP-4/5 (Pair)	Ramps for Linebacker CP5X125 and CP4X125 (2 Ramps and 4 Connectors)	Blue or Black	36 in. (914.4 mm)	21.88 in. (555.75 mm)	2 in. (50.8 mm)	40 lbs. (18.1 kg)
CPADARL-4/5 (Each)	Rail for Linebacker CPADARP-4/5	Yellow or Orange	1.5 in. (38.1 mm)	55.5 in. (1409.7 mm)	2 in. (50.8 mm)	12.75 lbs. (5.8 kg)
CPADARP-5GP (Pair)	Ramps for Linebacker CP5X125-GP (2 Ramps and 4 Connectors)	Blue or Black	36 in. (914.4 mm)	21.88 in. (555.75 mm)	2 in. (50.8 mm)	40 lbs. (18.1 kg)
CPADARL-5GP (Each)	Rail for Linebacker CPADARP-5GP	Yellow or Orange	1.5 in. (38.1 mm)	54 in. (1371.6 mm)	2 in. (50.8 mm)	12.7 lbs. (5.8 kg)
CPADARP-1GP (Pair)	Ramps for Linebacker CP1X125-GP (2 Ramps and 4 Connectors)	Blue or Black	36 in. (914.4 mm)	21.88 in. (555.75 mm)	2 in. (50.8 mm)	40 lbs. (18.1 kg)
CPADARL-1GP (Each)	Rail for Linebacker CPADARP-1GP	Yellow or Orange	1.5 in. (38.1 mm)	47.5 in. (1206.6 mm)	2 in. (50.8 mm)	12.65 lbs. (5.75 kg)
CPADARP-5GD (Pair)	Ramps for Guard Dog GD5X125 (2 Ramps and 4 Connectors)	Blue or Black	36 in. (914.4 mm)	21.88 in. (555.75 mm)	2 in. (50.8 mm)	40 lbs. (18.1 kg)
CPADARL-5GD (Each)	Rail for Guard Dog CPADARP-5GD	Yellow or Orange	2 in. (50.8 mm)	55.5 in. (1410 mm)	2 in. (50.8 mm)	12.75 lbs. (5.8 kg)
CPADARP-3GD-DO (Pair)	Ramps for Guard Dog GD3-DO (2 Ramps and 4 Connectors)	Blue or Black	36 in. (914.4 mm)	21.88 in. (555.75 mm)	2 in. (50.8 mm)	40 lbs. (18.1 kg)
CPADARL-3GD-DO (Each)	Rail for Guard Dog CPADARP-3GD-DO	Yellow or Orange	2 in. (50.8 mm)	55.5 in. (1410 mm)	2 in. (50.8 mm)	12.75 lbs. (5.8 kg)

WARNING! Cross-Guard™ ramps and rails are compatible only with Linebacker® and Guard Dog® cable protectors as specified. Improper use with other cable protector brands may result in product failure or injury.

SPECIFICATION DATA	
Material.....	Polyurethane (UV stabilized)
Operating Temp....	-40°F to 120°F (-40°C to 48°C)

LOAD CAPACITY PER TIRE/AXLE	
Capacity	Max Load 70°F (21°C)
Ramps	10,500 lbs./Tire (4,763 kg) 21,000 lbs./Axle (9,526 kg)

ADA Compliant Symbols Molded into Each Ramp

