

## ACCESS RAMPS AND RAILS



### ADA COMPLIANT

Cross-Guard™ ADA Compliant Ramps and Rails feature a gentle slope and slip resistant ramps to provide a safe crossing point for wheelchairs, carts and vehicles with small wheels. These ramps and rails can also be used in conjunction with Cross-Link Protector Bridges.

- Compatible with select Linebacker® & Guard Dog® Protectors
- Lightweight, 36" wide, modular ADA compliant ramps
- Quick attachment to one or multiple cable protectors
- Side rails provide ADA compliant edge protection
- Add ramps and rails whenever requirements specify
- Does not prevent accessibility to cables and cords
- One person installation - no tools required

### FOR SPECIFIC STYLES OF LINEBACKER® AND GUARD DOG® CABLE PROTECTORS



#### ◀ Carnival Midway Safety...

**LINEBACKER®**  
Cable Protectors and ADA compliant ramps have "Greatly improved the safety and accessibility of our carnival midway" and "are one of the greatest improvements to hit our midway in years."

- Gehrie Aten, President  
Bill Hames Shows, Inc.

| MODEL                 | DESCRIPTION   | COLOR            | A-WIDTH           | B-LENGTH              | C-HEIGHT        | WEIGHT               |
|-----------------------|---|------------------|-------------------|-----------------------|-----------------|----------------------|
| CPADARP-4/5 (Pair)    | Ramps for Linebacker CP5X125 and CP4X125 (2 Ramps and 4 Connectors) | Blue or Black    | 36 in. (914.4 mm) | 21.88 in. (555.75 mm) | 2 in. (50.8 mm) | 40 lbs. (18.1 kg)    |
| CPADARL-4/5 (Each)    | Rail for Linebacker CPADARP-4/5                                     | Yellow or Orange | 1.5 in. (38.1 mm) | 55.5 in. (1409.7 mm)  | 2 in. (50.8 mm) | 12.75 lbs. (5.8 kg)  |
| CPADARP-5GP (Pair)    | Ramps for Linebacker CP5X125-GP (2 Ramps and 4 Connectors)          | Blue or Black    | 36 in. (914.4 mm) | 21.88 in. (555.75 mm) | 2 in. (50.8 mm) | 40 lbs. (18.1 kg)    |
| CPADARL-5GP (Each)    | Rail for Linebacker CPADARP-5GP                                     | Yellow or Orange | 1.5 in. (38.1 mm) | 54 in. (1371.6 mm)    | 2 in. (50.8 mm) | 12.7 lbs. (5.8 kg)   |
| CPADARP-1GP (Pair)    | Ramps for Linebacker CP1X125-GP (2 Ramps and 4 Connectors)          | Blue or Black    | 36 in. (914.4 mm) | 21.88 in. (555.75 mm) | 2 in. (50.8 mm) | 40 lbs. (18.1 kg)    |
| CPADARL-1GP (Each)    | Rail for Linebacker CPADARP-1GP                                     | Yellow or Orange | 1.5 in. (38.1 mm) | 47.5 in. (1206.6 mm)  | 2 in. (50.8 mm) | 12.65 lbs. (5.75 kg) |
| CPADARP-5GD (Pair)    | Ramps for Guard Dog GD5X125 (2 Ramps and 4 Connectors)              | Blue or Black    | 36 in. (914.4 mm) | 21.88 in. (555.75 mm) | 2 in. (50.8 mm) | 40 lbs. (18.1 kg)    |
| CPADARL-5GD (Each)    | Rail for Guard Dog CPADARP-5GD                                      | Yellow or Orange | 2 in. (50.8 mm)   | 55.5 in. (1410 mm)    | 2 in. (50.8 mm) | 12.75 lbs. (5.8 kg)  |
| CPADARP-3GD-DO (Pair) | Ramps for Guard Dog GD3-DO (2 Ramps and 4 Connectors)               | Blue or Black    | 36 in. (914.4 mm) | 21.88 in. (555.75 mm) | 2 in. (50.8 mm) | 40 lbs. (18.1 kg)    |
| CPADARL-3GD-DO (Each) | Rail for Guard Dog CPADARP-3GD-DO                                   | Yellow or Orange | 2 in. (50.8 mm)   | 55.5 in. (1410 mm)    | 2 in. (50.8 mm) | 12.75 lbs. (5.8 kg)  |

**WARNING!** Cross-Guard™ ramps and rails are compatible only with Linebacker® and Guard Dog® cable protectors as specified. Improper use with other cable protector brands may result in product failure or injury.

#### SPECIFICATION DATA

Material..... Polyurethane (UV stabilized)  
Operating Temp.... -40°F to 120°F (-40°C to 48°C)

#### LOAD CAPACITY PER TIRE/AXLE

Capacity Max Load 70°F (21°C)  
Ramps 10,500 lbs./Tire (4,763 kg)  
21,000 lbs./Axle (9,526 kg)



ADA Compliant Symbols  
Molded into Each Ramp

