

Available from:

# CablesPlus


U \* S \* A

Cables Plus, LLC

8504 Glazebrook Ave Richmond, VA 23228 -- Toll Free (866) 678-5852

www.CablesPlusUSA.com

# KF-221FX Ver.C



## 100Base-FX Fast Ethernet PCI Adapter

### Ordering Information:

Model	Fiber Mode	Connector	Ref. Distance
KF-221FX-T	MM	Dual ST	2km
KF-221FX-C	MM	Dual SC	2km
KF-221FX-JM	MM	MT-RJ	2km
KF-221FX-VM	MM	VF-45	2km
KF-221FX-SA2	SM	Dual SC	20km
KF-221FX-SL2	SM	Dual SC	20km
KF-221FX-SL3	SM	Dual SC	30km
KF-221FX-SL4	SM	Dual SC	40km
KF-221FX-W3515	SM	Bi-Di SC	15-20km
KF-221FX-W5315	SM	Bi-Di SC	15-20km

MM: Multimode Fiber

SM: Single Mode Fiber

Ref. Distance: Reference connection distance

### Key Features:

- PCI revision 2.1 and 2.2 compliance
- 32-bit PCI half-card supports standard PCI
- Supports 100Base-FX fiber connection
- Complies with IEEE 802.3u 100Base-FX standard
- Supports diversified fiber connectors
- Far End Fault support on the 100Base-FX port
- Wake-On-LAN (WOL) function for ACPI-compliant systems
- Supports plug-and-play installation for Windows XP/2000/ME/2003 systems
- Supports network drivers for most popular operating systems
- Optional PXE/RPL Boot ROM for network operating systems

### Specifications:

Fiber Connectors	MM : ST, SC, MT-RJ, VF-45, LC & SM : SC
LEDs	100M Link, Act, Duplex
ACPI std.	Rev.1.1
PCI Power Management	Rev.1.1
DMI	Ver.2.0
PXE/RPL	PXE Ver.2.1
Environment	Operation Temperature: 0°C ~ 40°C Relative Humidity: 10% ~ 90% non-condensing
Dimension	130 x 65 mm

### Fiber Optical Specifications:

Model	Connector	FiberCable	Wavelength	Tx Power	Sensitivity	Rx Max.
-T	ST Duplex	MMF	1310nm	-19~ -14dBm	-31dBm	-14dBm
-C	SC Duplex	MMF	1310nm	-19~ -14dBm	-31dBm	-14dBm
-JM	MT-RJ	MMF	1310nm	-19~ -14dBm	-31dBm	-14dBm
-VM	VF-45	MMF	1310nm	-20~ -14dBm	-31dBm	-14dBm
-SA2	SC Duplex	SMF	1310nm	-15~ -8dBm	-31dBm	-7dBm
-SL2	SC Duplex	SMF	1310nm	-15~ -7dBm	-32dBm	-3dBm
-SL3	SC Duplex	SMF	1310nm	-15~ -8dBm	-34dBm	0dBm
-SL4	SC Duplex	SMF	1310nm	-5~ 0dBm	-34dBm	-3dBm
-W3515	Bi-Di SC	SMF	TX 1310nm RX 1550nm	-14~ -8dBm	-31dBm	0dBm
-W5315	Bi-Di SC	SMF	TX 1550nm RX 1310nm	-14~ -8dBm	-31dBm	0dBm

MMF : Multimode fiber 62.5/125 μm,50/125 μm

SMF : Single Mode fiber 9 /125 μm

Available from:

# CablesPlus

U \* S \* A

Cables Plus, LLC  
8504 Glazebrook Ave Richmond, VA 23228 ~ Toll Free (866) 678-5852  
www.CablesPlusUSA.com