

## WaveTester / WaveSource 850/1300/VFL Test Kit

## Multimode Fiber Certification Test Kit

### Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and guarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hard-copy documentation as proof of adherence to standards.

The **WaveTester / WaveSource 850/1300/VFL Test Kit** contains the tools necessary for certifying fiber optic links against a myriad of popular cabling standards in multimode networks.

The **WaveTester optical power meter** is multimode and singlemode ready, and can store reference values for all wavelengths used for optical loss measurements. Up to 100 fiber runs may be stored, and serially downloaded to a PC for report generation using our OWL Reporter software.

The **WaveSource 850/1300/VFL** is a multimode light source. Its dual wavelength outputs (850 nm & 1300 nm) are temperature-stabilized for accurate measurements. A Visual Fault Locator is also included for near-end visual fault location and visual fiber identification. Two connector options are available (ST or SC).



### Features

- Certification of multimode fiber links at 850 nm and 1300 nm
- Auto-test functions store references and data points automatically
- Data storage for up to 100 data points
- RS-232 interface for continuous data logging, report printing, or data downloading
- OWL Reporter software for printing formatted fiber certification reports
- Measurement modes include absolute (for optical power) or relative (for optical loss)
- Near-end visual fault location
- Visual fiber identification
- Selectively view, delete or resample data points

### Supported Cabling Standards:

EIA/TIA 568-B	ISO/IEC 11801
1000Base-SX	1000Base-LX
100Base-FX	10Base-FB
10Base-FL	FDDI
ATM-155	ATM-622
Fibre Channel	Token Ring


### Additional Power Meter Calibrated Wavelengths:

1310nm	1550nm
--------	--------

### Kit Contents

<b>Power Meter:</b>	WaveTester
<b>Light Source:</b>	WaveSource 850/1300/VFL
<b>Accessories:</b>	OWL Reporter software
	Product manuals
	Download cable
	9-volt batteries
	NIST certificate
	Carrying case
	Protective rubber boots

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.



Carrying cases and patch cables are available for an additional charge. Call 262-473-0643 for more information.

Available from:

# CablesPlus

U ★ S ★ A

Cables Plus, LLC

8504 Glazebrook Ave Richmond, VA 23228 ~ Toll Free (866) 678-5852

www.CablesPlusUSA.com

## WaveTester / WaveSource 850/1300/VFL Test Kit

Multimode Fiber Certification Test Kit

### Specifications

#### WaveTester Optical Power Meter

<b>Detector Type</b>	Ge
<b>NIST Traceable Wavelengths</b>	850 nm, 1300nm, 1310nm, 1550nm
<b>Measurement Range</b>	+5 to -60 dBm
<b>Accuracy</b>	±0.15 dB
<b>Resolution</b>	0.01 dB
<b>Connector Type</b>	2.5mm fixed Universal
<b>Data Storage Points</b>	up to 100
<b>Download Data Points</b>	OWL Reporter Software
<b>Power Units Displayed</b>	dBm, dB, $\mu$ W
<b>Battery Life</b>	250 hrs. (9v alkaline)
<b>Battery Capacity Display</b>	Yes
<b>Backlight</b>	Yes
<b>NIST Traceable</b>	Yes
<b>Auto-shutdown</b>	Yes
<b>Operating Temperature</b>	-10 to 55 C
<b>Storage Temperature</b>	-30 to 70 C
<b>Width</b>	2.75"
<b>Height</b>	4.94"
<b>Depth</b>	1.28"
<b>Weight</b>	154g

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

#### WaveSource 850/1300/VFL Multimode Light Source

<b>Launch Method</b>	LED
<b>Connector</b>	ST or SC
<b>Center Wavelength (850 nm)</b>	850 +30/-10 nm
<b>Center Wavelength (1300 nm)</b>	1300 $\pm$ 50 nm
<b>Spectral Width (FWHM; 850 nm)</b>	50 nm
<b>Spectral Width (FWHM; 1300 nm)</b>	180 nm
<b>Output Power</b>	-20.0 dBm
<b>Initial Accuracy</b>	0.1 dB
<b>Fiber Type</b>	multimode
<b>Battery Capacity Display</b>	Yes
<b>Operating Temperature</b>	-20 to +70° C
<b>Storage Temperature</b>	-40 to +85° C
<b>Width</b>	2.75"
<b>Height</b>	4.94"
<b>Depth</b>	1.28"
<b>Weight</b>	154g

#### Visual Fault Locator Specifications

<b>Launch Method</b>	Laser
<b>Center Wavelength</b>	650 nm
<b>Output Power</b>	-2.0 dBm
<b>Fiber Type</b>	multimode

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

Available from:

# CablesPlus

U ★ S ★ A

Cables Plus, LLC

8504 Glazebrook Ave Richmond, VA 23228 ~ Toll Free (866) 678-5852

www.CablesPlusUSA.com