



KS-105F, KS-108F



10/100 Fast Ethernet Switches with 1 Fiber Connection

Key Features:

- Provide 4/7 10/100Mbps Fast Ethernet Switch ports and 1 100Base-FX port
- Each TP port supports auto-negotiation and auto-MDI/MDI-X detection
- For the 100Base-FX fiber port, the switch series supports variety of fiber connectors for different application needs. The fiber connectors include ST, SC, MT-RJ, LC and VF-45 types for multimode and single mode fiber cables
- Support duplex mode selector for the 100BASE-FX fiber port
- Self learning for active MAC addresses and address aging
- Store-and-forward switching to ensure only good packets are forwarded
- Forwarding and filtering at full wire speed
- Support IEEE 802.3x flow control for full-duplex mode and backpressure flow control for half-duplex mode
- Comprehensive LED indicators provide quick, easy to read port and switch information

Specifications:

10/100 Ports	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX std. Shielded RJ-45 jacks with Auto MDI-X detection Auto-negotiation capable Speed for 10Mbps or 100Mbps Full-duplex or half-duplex mode support
100FX Port	IEEE 802.3u 100BASE-FX compliant Fixed 100Mbps operation Duplex mode selector - full-duplex or half-duplex
Flow control	IEEE 802.3x pause packet for full-duplex operation Back-pressure for half-duplex operation
Cables	10Base-T: Cat. 3, 4, 5 or higher (100 meters max.) 100Base-TX: Cat. 5, 5e or higher (100 meters max.) 100Base-FX: multimode or single mode fiber cable
LEDs	Power status Per port: Speed, Link, Activity, Duplex, Collision status
Forwarding rate	14,880 pps for Ethernet (10M) 148,800 pps for Fast Ethernet (100M)
Filtering address	Multicast/Broadcast/Unicast address
MAC Address Table	1K entries
Aging time	KS-105F: 300 seconds KS-108F: 240 seconds



Ordering Information:

KS-105F KS-108F	Fiber Mode	Connector	Ref. Distance
-T	MM	Dual ST	2km
-C	MM	Dual SC	2km
-JM	MM	MT-RJ	2km
-VM	MM	VF-45	2km
-SA2	SM	Dual SC	20km
-SL2	SM	Dual SC	20km
-SL3	SM	Dual SC	30km
-SL4	SM	Dual SC	40km
-W3515	SM	Bi-Di SC	15~20km
-W5315	SM	Bi-Di SC	15~20km

MM: Multimode Fiber
SM: Single Mode Fiber
Ref. Distance: Reference connection distance



FCC Part 15, Class A
CISPR 22 Class A

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd., Hsi-chih, Taipei Hsien, Taiwan.
Tel: 886-2-2698-3878
Fax: 886-2-2698-3873
E-mail: kti@ktinet.com.tw
URL: http://www.ktinet.com.tw

KTI Networks Inc.

7400 Harwin Dr., Suite 120 Houston, Texas
77036 U.S.A.
Tel: 713-266-3891
Fax: 713-914-0555
E-mail: kti@ktinet.com
URL: http://www.ktinet.com

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

Environment Operating Temperature: 0° ~ 40°C
Relative Humidity: 10% ~ 90% non-condensing

Dimensions KS-105F: 144 x 104.5 x 26 mm (WxDxH)
KS-108F: 180 x 114.5 x 26 mm (WxDxH)

DC IN Jack Rating +7.5V/1A, D6.3mm –  + D2.0mm

DC IN voltage Operating +6.0V ~ +12.6VDC (Device DC Input)

Power Consumption KS-105F: 3.9 watts. (max.)
KS-108F: 6.3 watts. (max.)

Fiber Optical Specifications:

Model	Connector	FiberCable	Wavelength	Tx Power	Sensitivity	Rx Max.
-T	ST Duplex	MMF	1310nm	-19~ -14dBm	-31dBm	-14dBm
-C	SC Duplex	MMF	1310nm	-19~ -14dBm	-31dBm	-14dBm
-JM	MT-RJ	MMF	1310nm	-19~ -14dBm	-31dBm	-14dBm
-VM	VF-45	MMF	1310nm	-20~ -14dBm	-31dBm	-14dBm
-SA2	SC Duplex	SMF	1310nm	-15~ -8dBm	-31dBm	-7dBm
-SL2	SC Duplex	SMF	1310nm	-15~ -7dBm	-32dBm	-3dBm
-SL3	SC Duplex	SMF	1310nm	-15~ -8dBm	-34dBm	0dBm
-SL4	SC Duplex	SMF	1310nm	-5~ 0dBm	-34dBm	-3dBm
-W3515	Bi-Di SC	SMF	TX 1310nm RX 1550nm	-14~ -8dBm	-31dBm	0dBm
-W5315	Bi-Di SC	SMF	TX 1550nm RX 1310nm	-14~ -8dBm	-31dBm	0dBm

MMF : Multimode fiber 62.5/125 μm, 50/125 μm
SMF : Single Mode fiber 9 /125 μm